



Product

Submersible pump for use in highly corrosive industrial waste water.

Denomination

Product code 3060.390
 Installation P, T, S
 Impeller characteristic LT, MT, HT
 Discharge connection 2", 3"

Process data

Liquid temp. max +70° C
 Depth of immersion max 20 m
 The pH of the pumped liquid pH 3 - 12
 Liquid density max 1100 kg/m³
 Strainer hole size (MT) 12 mm

Motor data

Squirrel cage 3-phase induction motor.
 Frequency 50 Hz
 Insulation class H (+180° C)
 Voltage variation
 - continuously running max ± 5%
 - intermittent running max ± 10%
 Voltage imbalance between phases max 2%
 No. of starts/hour max 15

Cable

Direct-on-line start SUBCAB

Monitoring equipment

Thermal contacts

Material

Outer casing Stainless steel
 Impeller Stainless steel
 Pump housing Stainless steel
 Stator housing Stainless steel
 Strainer Stainless steel
 Shaft Stainless steel
 O-rings Fluorinated rubber

Mechanical face seals

Inner Ceramic/Carbon
 Outer Ceramic/Ceramic

Weight

Total (excl. cable) 40 - 43 kg

Options

Other cables

Accessories

Discharge connections, adapters, hose connections and other mechanical accessories.

Electrical accessories such as pump controller, control panels, starters, monitoring relays, cables.

Rating

3~
 Rated output 2.4 kW
 Speed of rotation 2760 rpm

Voltage V	Rated current A	Starting current A
220	9.0	43
380	5.2	25
400	5.1	21
415	4.8	22
440	4.5	23
500	3.9	21
550	3.5	18